

## SPECIFICATIONS

Performance			
Angle Measurement	Accuracy	1"	
	Measure Method(HZ/V)	Absolute, continuous, 4 path detective	
	Diameter of Encoder Disk	79mm	
	Minimum Reading	1"/0.1"	
	Compensator Type	Dual axis, liquid photoelectric	
	Compensator Accuracy	1"	
Distance Measurement	Compensator Range	±6'	
	Laser Output*1	Class 3R	
	Measuring Range	Prism*2	3500m
		Reflectorless*3	1000m
	Accuracy	Prism	±(1mm+1xppm•D)
		Reflectorless	D<500m: ±(2mm+2xppm•D) D>500m: ±(5mm+2xppm•D)
	Measuring Time	Prism	Fine: 0.3S, Tracking 0.1S
		Reflectorless	0.3-3S
Minimum Reading		1mm/0.1mm	
Robotic Specification			
Motorization	Motor Type	DC Servo Motor	
	Rotate speed	60°/s	
	Rotation Time F1/F2	2.9s	
Prism Search	Range	3-300m	
	Scope*4	Horizontal: 360°; Vertical: ±18°	
	Search Time	Typically 3.5s per 90°	
Auto Prism Recognition	Range*5	3-1200m	
	Time	3-5s	
	Search Window	Customized	
General Specification			
Telescope	Image	Erect	
	Tube Length	154mm	
	Effective Aperture	45mm (EDM: 50mm)	
	Magnification	30x	
	Resolving Power	3"	
	Field of View	1°30'	
	Minimum Focus	1.2m	
	Reticle Illumination	5 brightness levels	
OS, Interface and Data	Operation System	Android 11	
	Display	5inch, TFT color LCD with LED backlight, touch screen, dual face	
	Keyboard	13 keys with backlight, 4 keys for function	
	Processor	MT6833, 8 Core, 2.2GHz	
	Data Storage	Internal Memory Plug-in Memory Device	4GB RAM, 64GM ROM Type-C for USB OTG, TF card
Communication	Interface	RS-232, Bluetooth 5.1	
	WLAN	2.4G/5G/WIFI	
	SIM Slot	Micro Sim, 5G	
	Long-range Remote Control	Powered by Zigbee, 450m	
Levels	Plate Level	30"/2mm	
	Circular Level	8'	
Laser Plummet	Type	Red laser dot, 635nm	
	Accuracy	±1.5mm at 1.5m	
Power Supply	Operating Time (20°C)	4 hours	
	Battery	Li-ion rechargeable battery, 5400mAh	
Working Environment	Working Temperature	-20°C to +50°C	
	Storage Temperature	-40°C to +70°C	
	Protection /Humidity	IP54 / 95% non-condensing	
Dimension	Size	217mm*198mm*378mm (without antenna)	
	Weight	7kg (with battery)	

\*1: A built-in rangefinder product equipped with a Class 3R laser has a harmful distance of 1000m (3300ft). Beyond this distance, the laser intensity will be reduced to Class 1.

\*2: Standard clear, no haze, overcast situations. Range and accuracy are dependant on atmospheric conditions.

\*3: With Kodak Gray Card White Side (90% reflective)

\*4/5: For 64mm round prism.

**SOUTH**  
Target your success

**NS30**  
Robotic Total Station



- High accuracy - 1" for angle, 1+1ppm for distance
- Long range prism (3500m) and reflectorless (1000m) measurements
- Reliable prism search to 300m
- Auto prism recognition to 1200m
- LocknTrack function
- Hyper Drive, direct motor powered by worm and gear
- Flexible data transfer by USB OTG, TF card and Bluetooth
- Fully robotic control with H6 Plus Controller, up to 450m
- Practical Survey Star onboard

**SOUTH**  
Target your success

SOUTH SURVEYING & MAPPING TECHNOLOGY CO., LTD.

E-mail: mail@southsurvey.com


http://www.southinstrument.com

You Local Authorized Dealer

Version: NS30 1.0



# f - ... Š ‡ • Ž Ž ‹ • NS30



'LUHFW ORWRU E\ :RUP \*HDU  
6WDEOH DQG UHOLDEOH IRU PRWRULJDWLRQ  
3RVLWLRQLQJ DFFXUDF\ μ



:KHQ 3ULVP 6HDUFK LV DFWLYDWHG  
16 HQDEOHV \RX WR VHDFK  
UHFRJQLJH DQG DLP D SULVP LQ P  
ZLWK ERWK YHUVDWLOLW\ DQG DJLOLW\



16 IHDWXULQJ D SRZHUIXO DOJRULWKP  
WKDW DXWRPDWLFDOO\ DLP DQG UHFRJQLJH  
WKH SULVP ZLWKLQ WKH VLJKW RI YLHZ IRU  
P ,W FDQ KDQGOH HYHU\ WDVN ZLWK  
HDVH



:LWK /RFNQ73DVFNDVLHU WR ORFN  
RQWR WKH SULVP DQG IROORZ LWV  
PRYHPHQWV FRQVWDQWO\ ZKLFK LV DEOH  
WR HOLPLQDWH WKH QHGH IRU VWDQG  
DURXQG DQG ZDLWLQJ ZKHQ FROOHFWLQJ  
GDWD RU VWDNLQJ RXW




- =LJEHH DQWHQQD IRU P IXOO\ URERWLF UHPRWH FRQWURO
- 6HDPOHVV GDWD WUDQVIHU ZLWK %OXHWRRWK
- (DV\ DFFHVV WR QHWZRUN GXDO QDQR VLP FDUG DQG :\$180WUD )OH[LEOH
- LQFKHV FDSDFLWLYH WRXFK VFUHHQ
- \$QGURLG RSHUDWLQJ V\ VWHP \*% 520
- )XOO\ NH\SDG IRU TXLFNHU HQWU\
- :DWHUSURRI DQG GXVWSURRI ,3 GHVLJQ
- 0DUNHW OHDGLQJ KRXUV EDWWHU\ ZRUNLQJ OLIH DQG

# NS30


Š ‡ Ž - ‹ • f - ‡ • ‡ æ f •

%HQHILW IURP =LJEHH WHFKQRORJ\ 16 FDQ  
ZLWK \RXU + 30XV &RQWUROOHU LQ PD[LPXP  
/RQJ UDUQH GDWD OLQN RIIHUV D IOH[LEOH DQ  
IRU RQH PDQ VXUYH\ V\ VWHP


3UDFWLFDO 2QERDUG 6RIWZDUH 6XUYH\



6XUYH\ 6WUDQSV \RX FROOHFW  
GDWD DQG VWDNH RXW HIILFL  
JUDSKLFDO DQG LFRQLF JXLG




0DS 'ULYHQ :RUNIORZ  
,W LV DQ LQWUDFWLYH IXQF  
HPEHGGHG LQ 6XUYH\ 6WUDQ  
YLVLEOH IHDWXUH



1RW QHFHVVDU\ WR H[WUDFW  
FRRUGLQDWH IURP &\$' ILOHV  
PRUH 7KH RQO\ WKLQJ \RX Q  
GR LV LPSRUW WKH &\$' ILOHV  
WR VWDNH RXW WKH SRLQW

)OH[LEOH &ROOHFWRU 6RIWZDUH 6XUYH\



6XUYH\ 6WUDQ 3LORW LV D SRZ  
DQG SUDFWLFDO ILHOG VRIWZ  
IRU 16 LW HQDEOHV \RX WR  
FKDQJH WKH VHWWLQJ FROO  
DQG VWDNH RXW SRLQW HDV  
\RXU FRQWUROOHU



80WUD )DVW  
(IILFLHQW IRU UG 3DUW\ 'HYHORSHU)OH[LELOLW\ 0DNHV ,W (DV\ WR 6WUDQ  
&RPELQH ZLWK 6XUYH\ 6WUDQ 3LORW<RX MXVW QHGH WR FDUU\ D SULVP S  
RIIHUV D IOH[LEOH ZRUNIORZ \$OVR LW XSWR RQOHU WKHQ \RX FDQ Y  
WKH VRIWZDUH VXLWH ZKLFK FDQ EHSRHOVSHQO\ RQH SHUVRQ 1RW G  
E\ \RXU RZQ UHTXHVWV )DVWU DQGFRDFKQVWV ZLWK RSHUDWRU DW V  
QRFDWHV SRLQW IURP SRLQW WR ILHOGWXPVWV JMXVW IROORZLQJ WKH  
16 URERWLF WRWDO VWDWLRQ \RXU FRQWUROOHU